

	<p>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</p>	
TANK TRAILER SPECIFICATION		
<b>PRODUCT</b>	<b>R-TERTIARY BUTYL ETHER R-TBE</b>	
Material Characteristic and immediate hazard	See Product SDS	
DOT SPECIFICATION	MC 307, DOT 407 (STAINLESS STEEL TRAILER)	
INSULATION	PREFERRED BUT NOT REQUIRED	
HEATING CAPABILITIES	NOT REQUIRED	
GASKET MATERIAL	VIRGIN TEFLON , TEFLON ROPE, TEFLON INCAPSULATED, **DOME GASKET MUST PROVIDE A LEAK TIGHT SEAL UPON COMPLETION OF LOADING	
CONNECTIONS/FITTINGS	ALL MUST BE STAINLESS STEEL, W/DUST CAP, W/SEAL PONTS, DOME LID AND ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL	
LIQUID CONNECTION	3 "MALE CAMLOCK (QUICK CONNECT), W/DUST CAP - BOTTOM REAR LOADER (CENTER LOADER WILL REQUIRE APPROVAL). <b>NOTE:</b> CUSTOMER MAY HAVE SPECIFIC EQUIPMENT REQUIREMENTS FOR DELIVERY. MUST BE EQUIPPED FOR SEALING WITH AN 1/8" WIRE CABLE SEAL.	
VAPOR CONNECTION	2" MALE CAMLOCK (QUICK CONNECT), W/DUST CAP, WITH PIPING TO GRADE LEVEL, WITH 2" SS ISOLATION VALVE , (INLINE PRESSURE GAUGE @ GRADE LEVEL PREFERRED). 2" WITH DUST CAP, (MUST BE ABLE TO SEAL). <b>NOTE:</b> STANDARD 3/4" TOP CONNECTION MAYBE ACCEPTABLE WITH PRIOR APPROVAL	
NITROGEN PADDING	5-7 PSIG NITROGEN PAD UPON ARRIVAL	
TANK CLEANLINESS	CLEAN TRAILER MUST BE CLEAN, DRY, AND ODOR FREE. IF NOT A DEDICATED TRAILER, A CLEANING OR RELOAD CERTIFICATE IS REQUIRED. NOTE: IF TRAILER IS RE-LOAD, A COPY OF THE PRIOR LYONDELLBASELL SHIPPING DOCUMENTS IS REQUIRED TO INDICATE THE SAME PRIOR PRODUCT	
STRAPPING CHART W/DRIVER	YES	
HOSES	HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING DOCUMENT.	
ADDITIONAL APPURTENANCES	NONE, CARRIER SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY ADDITIONAL EQUIPMENT, DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENINGS TO THE TRAILER MUST BE CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE SEAL.	
OTHER	MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. **DRIVER MUST ALWAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING DUE TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS	
PROHIBITED	NO ADDITIONAL PERSONNEL, UNLESS TEAM DRIVERS, PETS ARE PROHIBITED	