

	<p>These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading a tank trailer at a LyondellBasell site or a contracted 3PL location as applicable</p>	
<p>TANK TRAILER SPECIFICATION</p>		
<p>PRODUCT</p>	<p>TERT-BUTYL HYDROPEROXIDE (TBHP)</p>	
<p>Material Characteristic and immediate hazard</p>	<p>See Product SDS</p>	
<p>DOT SPECIFICATION: (NORTH AMERICA ONLY)</p>	<p>MC 312/DOT 412 - DEDICATED TO TERT-BUTYL HYDROPEROXIDE SERVICE AND DEDICATED TO A SINGLE CARRIER (DANA TRANSPORT) DEDICATED TRAILERS #: D-792, D-793, D-4370, D-4371, D-4372, D-4373, D-4375. ANY EQUIPMENT FOR TBHP SERVICES MUST BE APPROVED</p>	
<p>INSULATION/HEATING</p>	<p>INSULATION REQUIRED; HEATING NOT REQUIRED</p>	
<p>GASKET MATERIAL</p>	<p>TEFLON, KALREZ, OR SIMRIZ 7295 ONLY; MUST BE IN ALL FLANGES AND OPENING TO TRAILER</p>	
<p>CONNECTIONS/FITTINGS</p>	<p>ALL MUST BE STAINLESS STEEL, DUST CAPS W/SEAL PONTS, ALL VALVES MUST BE CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE</p>	
<p>LIQUID CONNECTION</p>	<p>3" MALE KAMLOK ADAPTER - LIQUID PIPING MODIFIED TO BOTTOM REAR GRADE LEVEL @ 90° ANGLE FOR LOADING. MUST HAVE 2 ISOLATION VALVES; 1 CLOSE TO TRAILER AND THE OTHER UPSTREAM OF THE LIQUID CONNECTION.</p>	
<p>VAPOR CONNECTION</p>	<p>2" MALE KAMLOK ADAPTER - VAPOR PIPING MODIFIED TO BOTTOM REAR GRADE LEVEL @ 90° ANGLE FOR VENTING W/ISOLATION VALVE.</p>	
<p>NITROGEN PADDING</p>	<p>YES, MINIMUM 15 PSIG ON CLEAN OR RE-LOAD UPON ARRIVAL</p>	
<p>TANK CLEANLINESS</p>	<p>ALL TANK TRAILER SHOULD BE DEDICATED. IF A TANK TRAILER HAS TO BE CLEANED, A CLEANING CERTIFICATE MUST BE SENT WITH TRAILER. TRAILER MUST BE PROPERLY FILLED WITH SADDLES. NOTE: A MAINTENANCE CERTIFICATE MUST ALSO BE WITH TRAILER THAT INDICATED THE TYPE OF MAINTENANCE PERFORMED</p>	
<p>STRAPPING CHART W/DRIVER</p>	<p>YES</p>	
<p>HOSES</p>	<p>HOSE(S) ARE NOT REQUIRED AT LYONDELLBASELL LOADING FACILITIES. PLEASE NOTE: THERE MAY BE SPECIFIC HOSE(S) REQUIREMENTS FOR CUSTOMER THAT SHOULD BE NOTED IN THE CARRIER INSTRUCTIONS OF THE LYONDELLBASELL SHIPPING</p>	
<p>ADDITIONAL APPURTENANCES</p>	<p>DOME LID MUST BE A SOLID BOLTED FLANGE; TANK TRAILERS ARE CUSTOMED MODIFIED BY CARRIER. TRAILER MUST HAVE AN EMERGENCY SHUT-OFF ON LIQUID LINE NEAR TRAILER. SPECIAL NOTE: RETURN SEALS MUST BE SENT WITH DRIVER. DRIVER MUST ENSURE RETURN SEALS ARE INSTALLED EITHER BY DRIVER OR CUSTOMER. ALL FLANGES AND SCREWED FITTING MUST BE SEALED CLOSED. TRAILER MUST BE EQUIPPED WITH TEMPERATURE GAUGE</p>	
<p>OTHER</p>	<p>TRAILERS ARE TO BE TRANSPORTED BY DANA TRANSPORT DRIVERS ONLY. MUST HAVE SAP CURRENT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR CARRIER MANIFEST DOCUMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED TIME. PLEASE CONTACT LYONDELLBASELL LOGISTICS WITH ANY QUESTIONS. SPECAIL REQUIREMENT: TRAILER MUST HAVE THE PROPER AMOUNT OF SADDLES AND A VALID SP-6610 PERMIT</p>	
<p>PROHIBITED</p>	<p>NOTE: NO CUSTOMER PICKUP; TERT-BUTYL HYDROPEROXIDE WILL ONLY BE LOADED INTO LYONDELLBASELL DEDICATED TANK TRAILERS LISTED. NO PETS OR ADDITIONAL PERSONNEL UNLESS THEY ARE TEAM DRIVER. PETS ARE PROHIBITED</p>	